



Code	Description	Size	Colour
56502	Toptec Flash Fix Sealant Tape	150mm x 25m	Aluminium
56605	Toptec Flash Fix Sealant Tape	50mm x 3m	Aluminium
56607	Toptec Flash Fix Sealant Tape	100mm x 3m	Aluminium
56608	Toptec Flash Fix Sealant Tape	50mm x 10m	Aluminium
56609	Toptec Flash Fix Sealant Tape	75mm x 10m	Aluminium
56610	Toptec Flash Fix Sealant Tape	100mm x 10m	Aluminium

Description

Toptec Flash Fix Sealant Tape is based on SBS modified rubberised asphalt with a solid aluminium foil backing, ideal for sealing and weatherproofing of joints.

Characteristics

- Adheres to a wide range of substrates.
- Excellent weatherproofing protection
- High Bond Strength
- Good UV resistant
- Permanent elastic after curing
- Suitable for above and below ground application

Technical Data

<i>Total Thickness \pm 10%:</i>	1.5 mm
<i>Tensile Strength:</i>	>5 kg/25mm
<i>Elongation:</i>	>100 %
<i>Test Method:</i>	ATSM D-1000
<i>Adhesion to Steel:</i>	>0.35 kg/25mm
<i>Unwind Force:</i>	>0.65 kg/25mm
<i>Application Temperature Range:</i>	+5°C → 30°C

Applications

- Weather sealing of joints,
- Sealing around corner details, inside balcony details, detailing around drainage fittings.

Shelf Life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Application

Substrates:	all usual building substrates, insulated panel, masonry, Fibre Cement, metals and many membrane systems (<i>testing is required especially prior to using with membranes</i>)
Nature:	clean, dry, free of dust and grease.
Surface preparation:	All Non-Porous should be wiped with Toptec Express Cleaner There is no/limited adhesion on PE, PP, PTFE (Teflon®)
Cleaning:	Toptec Express Cleaner

Toptec recommends preliminary compatibility tests prior to application.

Remarks:

- Do not use on natural stones like marble, granite (staining).
- Direct contact with the primary sealing of double glazing units (insulation) and the PVB-film of safety glass must be avoided.
- Do not use on polycarbonate.
- Should not be applied directly over (in contact with) polyurethane, MS Polymer and Silicone sealants

Health and Safety Recommendation

- Apply the usual industrial hygiene.
- Take the usual labour hygiene into account. Consult the packaging label for more information.

Remark

The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

If any clarification is required, please contact 0800 TOPTEC or email sales@toptec.co.nz

Last Updated: 23 January 2019